CLA-LS
ACCESSORIES



DESCRIPTION

Visual level indicators

MATERIALS

Transparent part: Trogamid T
Anti-shock protection: Painted steel
Fixing bolts: zinc plated steel
Seals: NBR Nitrile
(FKM - on request fluoroelastomer)

Double scale thermometer
(Celsius and Farenheit) option available.
Tightening torque for the fixing bolts 10 Nm

PRESSURE


Max pressure allowed 100 kPa (1 bar)

WORKING TEMPERATURE

From -20°C to +90°C



HYDRAULIC DIAGRAM



Is this datasheet the latest release? Please check on our website.

CLA-LS
ACCESSORIES

ORDERING AND OPTION CHART

C	L	A				
			SIZE & LENGTH	11	12	13
		M	CONNECTION TYPE			
			M = metric thread	M	M	M
			CONNECTION SIZE			
			10 = M10	10	10	10
			12 = M12	12	12	12
		N	SEALS			
			N = NBR Nitrile	N	N	N
			ACCESSORIES			
			W = without	W	W	W
			T = with thermometer	T	T	T

DIMENSIONS

	H1	H2	H3	D
CLA11M10NW LS0761WM10	108	76	32	M10
CLA11M10NT LS0761TM10	108	76	32	M10
CLA12M12NW LS1271WM12	160	127	75	M12
CLA12M12NT LS1271TM12	160	127	75	M12
CLA13M12NW LS2541WM12	286	254	192	M12
CLA13M12NT LS2541TM12	286	254	192	M12

