DELTA HYDRO

SNS2 EXTREME

Wąż wysokociśnieniowy

Wąż hydrauliczny typ: **SNS2 EXTREME EN 853 2SN**
Hydraulic hose type: **SNS2 EXTREME EN 853 2SN**

Opis:

• Wąż dla wysokociśnieniowych systemów hydraulicznych używających oleje hydrauliczne, smary mineralne i roślinne.
• Warstwa wewnętrzna: specjalna guma syntetyczna odporna na oleje mineralne, roślinne i hydrauliczne.
• Warstwa zewnętrzna: specjalna guma syntetyczna odporna na oleje, ścieranie i warunki atmosferyczne, antystatyczna odporna na ogień.
• Wzmocnienie: 2 oplot stalowy o wysokiej wytrzymałości.

• For high pressure hydraulic systems using hydraulic oils, mineral and vegetable lubricants.
• Tube: mineral, vegetable and hydraulic oil resistant special synthetic rubber.
• Cover: oil, abrasion and weather resistant special synthetic rubber.
• Reinforcement: 2 high tensile steel wire braids.

KOD / CODE / CODE	DN	ID	OD	WP	BP	R min	W	
		mm	mm	bar	bar	mm	g / m	
SMOOTH								
EXTREME062SN	**6**	6,2 - 6,6	14,4 ± 0,3	400,0	1600,0	100,0	370,0	**DH-UNI.06**
EXTREME082SN	**8**	7,7 - 8,1	16,0 ± 0,3	350,0	1400,0	115,0	420,0	**DH-UNI.08**
EXTREME102SN	**10**	9,3 - 9,7	18,7 ± 0,3	330,0	1320,0	125,0	560,0	**DH-UNI.10**
EXTREME122SN	**12**	12,5 - 12,9	21,8 ± 0,3	275,0	1100,0	180,0	640,0	**DH-UNI.12**
EXTREME162SN	**16**	15,7 - 16,1	24,8 ± 0,3	250,0	1000,0	205,0	770,0	**DH-UNI.16**
EXTREME192SN	**19**	18,8 - 19,2	29,1 ± 0,3	215,0	860,0	240,0	940,0	**DH-UNI.19**
EXTREME252SN	**25**	25,2 - 25,6	37,6 ± 0,3	165,0	660,0	300,0	1430,0	**DH-UNI.25**

Zakres temperatur / Temperature range: -40°C / +100°C. Markowanie / Marking: Taśma transferowa / Transfer tape.

SNS2 EXTREME DIN EN 853 2SN DN ... -...” WP ... BAR / BP ... BAR

Normy / Norms		Kolor / Colour	Czarny / Black	Czerwony / Red	Zielony / Green	Niebieski / Blue
	DIN EN 853 2SN, ISO1436		√			