

FLOW REGULATOR VALVE, 2FB95, 2FB95-G6W-95S

405AA00436A

Model code: 2FB95-G6W-95S

Where to buy

Product specifications

Characteristic	Value	Description
Adjustment type	NO OPERATOR	No Operator
Brand	DANFOSS	Danfoss
Factory set flow rate GPM		12.548
Factory set flow rate LPM		47.50
Flow rate GPM		25.096
Flow rate lpm		95.00
Fluid compatibility	MIL-H-5606, SAE10, SAE20, ETC	MIL-H-5606, SAE10, SAE20, etc
Function	FLOW REGULATOR	Flow Regulator
Housing	YES	Yes
Housing material	ALUMINUM	Aluminum
Installation type	SCREW-IN CARTRIDGE	Screw-in Cartridge
Leakage	STANDARD	Standard
Maximum flow rate GPM		25.100
Maximum flow rate LPM		95.00
Model Code 1		2FB95-G6W-95S
Number of housing ports	3	3
Number of valve ports	3	3
Operating temperature	-20 C TO 90 C (-4 TO 194 F)	-20 C to 90 C (-4 to 194 F)
Port Size	3/4"	3/4"
Port Type	BSP	BSP
Pressure rating BAR		210.00

Characteristic	Value	Description
Pressure rating PSI		3045.79
Product height in		4.370
Product height mm		110.998
Product length in		4.840
Product length mm		122.936
Product width in		1.490
Product width mm		37.846
Rec filtration level	18/16/13	18/16/13
Seal type	BUNA-N	Buna-N
Special features	NONE	None
Spool seal	NO	No
Style	FIXED PRESS COMPENS, FLOW REG	Fixed Pressure Compensated, Flow Regulator

For the most current information and other product assets, please use this link to visit the product page on PowerSource

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.